



renner[®]
A Beynon Sports Company

THE ULTIMATE
SURFACE EXPERIENCE

ACO SPORT DRAIN MAINTENANCE

The Maintenance Schedule shall be determined by the maintenance person who is responsible for the grounds maintenance at the athletic facility location where the ACO Sport Drain System is installed. The maintenance schedule can vary significantly due to location and use of facility (i.e., area with numerous trees, natural grass clippings, trash from grandstands etc.).

GRATED SYSTEM

Grate to be removed either by un-bolting the conventional locking device or by using the special QuickLok Removal Tool for Quicklok Grates. Visually inspect the polymer concrete channel for debris. The debris shall be extracted and/or flushed with water...by pushing the debris into the inline catch basin trash basket for retrieval. The trash basket shall be emptied of all solid matter and returned to the original position. Any removed grates shall be re-positioned and locked into place.

ACO Shovel Head, an optional tool, which is specially designed for channel cleanout is available and can be ordered to help clean the interior body of the channel.

SLOT CHANNEL SYSTEM

System shall be flushed with water through the slot opening by use of a garden hose and sprayer head or by a high pressure water sprayer. Debris shall be pushed to the inline catch basin trash basket for retrieval. The trash basket shall be emptied of all solid matter and returned to the original position. Any slot drain covers removed from the inline catch basins shall be returned to their original position.

Please contact Bob Hanefield, ACO Sport Product Manager at 800-993-2738 or ACO Polymer Products at 800-543-4764, if you require additional information or assistance.